

Glass Fiber Tape



TBJ-UTEX INDUSTRIES (M) SDN BHD

(Company No: 319073-P)
No 50, Jalan Sri Plentong 8,
Taman Perindustrian Sri Plentong,
81750 Masai, Johor Bahru, Johor.
Tel: 607-3863 777 Fax: 607-3868 777
Email: sales@tbj.com.my Website: www.tbj.com.my



MS ISO/IEC 17021:2011
QS26122016 CB 16



Certificate Number : FM 646287
ISO 9001 : 2015

Basis

Material is based on E-glass Filament (Fiberglass). It is designed to provide superior heat protection, electrical insulation, and chemical resistance for pipe wrapping, boiler seals, and exhaust insulation worldwide.

Applications

- Insulating steam lines
- Wrapping industrial exhaust pipes
- Heat shields
- Removable insulation covers
- Fire curtains
- Expansion joints

Dimensions of the

Sizes:

- Width: 20 – 200mm
- Thickness: 0.8 – 6mm

Technical Data

	Specified Value	Unit
Min. Temperature	450	°C
Max. Temperature	550	°C

All information/applications contained in these publications are to best of our product knowledge. Since condition of uses is beyond our control, users must satisfy themselves that products are suitable for the intended processes and uses. Failure of select the proper sealing products could result in property damage and/or serious personal injury. We reserve the right to change product information without notice.